



Grant Agreement: 287829

Comprehensive Modelling for Advanced Systems of Systems

C COMPASS

Fourth Release of the COMPASS Tool CML Grammar Reference

Deliverable Number: D31.4c

Version: 1.0

Date: September 2014

Public Document

<http://www.compass-research.eu>

Contributors:

Joey W. Coleman, Aarhus

Editors:

Joey W. Coleman, Aarhus

Reviewers:

Uwe Schulze, Bremen
Richard Payne, Newcastle
Adrian Larkham, Atego

Document History

Ver	Date	Author	Description
0.1	02-12-2013	JWC	Initial version based on D31.3c
0.2	08-07-2014	JWC	Update based on current grammar file & tool state.
0.3	16-07-2014	JWC	Remove stray action combinator
0.4	19-08-2014	JWC	Editing from internal review
1.0	01-09-2014	JWC	Ready for delivery

Contents

1 Introduction	5
1.1 Definition (Meta-)Syntax	5
1.2 Major changes relative to previous versions	6
2 Top Level model	7
3 Declarations	7
4 Classes	9
5 Processes	10
6 Actions	12
7 Statements	13
8 Types	15
9 Operations	17
10 Functions	18
11 Expressions	19
12 Patterns	22
13 Lexical Specification	23
References	27
Index	28

1 Introduction

The purpose of this document is to provide a reference for the grammar of the COMPASS Modelling Language (CML), as it is accepted by the Symphony IDE. This document is a reference document and, as such, makes no attempt to explain the purpose of any of the constructs that the defined syntax corresponds to, as this is not in the scope of the Theme 3 work. For the semantics of CML, please see [BCW14].

This document accompanies version 0.4.0 of the Symphony IDE, corresponding to the COMPASS Deliverable D31.4 release.

This document supports several useful activities:

1. users of the tool may use this document as a reference to ensure that their models conform to the format that the tool expects;
2. we can compare the syntax of the language the tool accepts against the semantic and syntactic definitions produced in Theme 2 for discrepancies; and,
3. members of the project have a basis for discussions regarding the superficial structure of the language that is neither the running code nor the semantics.

The second and third points were critical for maintaining the tool in the face of changes to the CML language as the project progressed. This document, in its previous versions, was used as a reference in to clarify conversations about both the tool and the language.

The first point is meant to be taken as a complement to tutorial materials, not as a replacement for them. The initial tutorials for CML are critical for users to gain an understanding of how to use the language; this document is intended to clarify the specific details of how to express models in CML.

1.1 Definition (Meta-)Syntax

The syntax used in this document to define the CML syntax is a variation of the usual Extended BNF syntax commonly used elsewhere. Rule definitions start with the name of the rule, then an equality symbol, =, then the rule definition body, then a semi-colon.

A rule definition body is a list of alternatives separated by vertical bars, |, and each alternative is a comma-separated list of components. Each component may be a literal string, which is a terminal symbol, a reference to another rule, or a bracketed sublist of components indicating either the optional presence of the sublist in that alternative, or the Kleene closure of the sublist. Examples of this are presented in [Figure 1](#).

The example rule presented in [Figure 2](#) uses all of the features permitted in our grammar format. It is named *example rule*, has two alternative productions, has terminal symbols and rule references, and uses the optional item and sequence braces.

Example	Explanation
<code>'literal'</code>	A literal value indicating the characters between the quotation marks.
<code>map expression</code>	A reference to the rule “ <i>map expression</i> ”.
<code>'inv', expression</code>	The literal characters <code>inv</code> followed by something satisfying the <i>expression</i> rule.
<code>{ bind }</code>	A (possibly empty) sequence of things, each satisfying the <i>bind</i> rule.
<code>[':', type]</code>	Either empty or the concatenation of a colon and then something that satisfies the <i>type</i> rule.

Figure 1: Examples of definition elements used in this document.

example rule →

```
'terminal symbol', example rule, { 'optional sequence' }
| 'alternative case', [ 'optional single' ]
;
```

Figure 2: An example grammar rule.

1.2 Major changes relative to previous versions

The proposed syntax for configuration blocks that previously appeared in Deliverable D31.3c [Col13] has been removed from this version. The impact should be minimal to non-existent: no models in the project used the syntax, only the parser implemented the necessary functionality, and only in an experimental branch.

All forms of synchronous parallelism –parallel combinators that do not have specify chansets, but not including interleaving– have been removed. Their inclusion was an oversight, as they were not intended to be a part of the CML language.

The divergent action keyword `'Div'` has been renamed `'Diverge'` due to a parsing/recognition problem. The chaotic action keyword `'Chaos'` has been removed from the language, in part because of a difference between the definition of that action between Hoare's and Roscoe's semantics for CSP. Using just `'Diverge'` suits the needs of the project and language, and avoids confusion.

2 Top Level model

model →
model paragraph, { *model paragraph* }
;

model paragraph →
type declarations
| *function declarations*
| *value declarations*
| *channel declarations*
| *chanset declarations*
| *class declaration*
| *process declaration*
;

3 Declarations

value declarations →
'values', { *value definition* }
;

value definition →
[*qualifier*], *bindable pattern*, [':', *type*], '=', *expression*
;

qualifier →
'private' | 'protected' | 'public' | 'logical'
;

channel declarations →
'channels', { *channel name declarations* }
;

channel name declarations →
identifier, { ',', *identifier* }, [':', *type*]
;

chanset declarations →

```
'chansets', { chanset definition }  
;
```

```
chanset definition →  
  identifier, '=', chanset expression  
;
```

```
nameset declarations →  
  'namesets', { nameset definition }  
;
```

```
nameset definition →  
  identifier, '=', nameset expression  
;
```

```
state declarations →  
  'state', { instance variable definition }  
;
```

```
instance variable definition →  
  [ qualifier ], assignment definition  
  | invariant definition  
;
```

```
assignment definition →  
  identifier, ':', type, [ '=', expression ]  
;
```

```
invariant definition →  
  'inv', expression  
;
```

```
process declaration →  
  'process', identifier, '=', [ parametrisation, { ',', parametrisation }, '@' ],  
  process  
;
```


Note: the only parametrisation qualifier allowed in a process declaration is ‘val’. (Omitting a parametrisation qualifier defaults to ‘val’, and is permitted as well.)

parametrisation →

[*parametrisation qualifier*], *identifier*, { ‘,’, *identifier* }, ‘:’, *type*
;

parametrisation qualifier →

‘val’ | ‘res’ | ‘vres’
;

action declarations →

‘actions’, { *action definition* }
;

action definition →

identifier, ‘=’, [*parametrisation*, { ‘,’, *parametrisation* }, ‘@’], *action*
;

chanset expression →

identifier
| ‘{’, [*identifier*, { ‘,’, *identifier* }], ‘}’
| ‘{|’, [*identifier*, { ‘,’, *identifier* }], ‘|}’
| ‘{|’, *identifier*, { ‘.’, *expression* }, ‘|’ *bind list*, [‘@’, *expression*], ‘|}’
| *chanset expression*, ‘union’, *chanset expression*
| *chanset expression*, ‘inter’, *chanset expression*
| *chanset expression*, ‘\’, *chanset expression*
;

nameset expression →

chanset expression
;

4 Classes

class declaration →

‘class’, *identifier*, [‘extends’, *identifier*], ‘=’, ‘begin’, { *class paragraph* }, ‘end’
;

class paragraph →
type declarations
 | *value declarations*
 | *function declarations*
 | *operation declarations*
 | *state declarations*
 | *'initial', operation definition*
 ;

5 Processes

process →
action process
 | *process, ';' , process*
 | *process, '[' , process*
 | *process, '|~|' , process*
 | *process, '[' , chanset expression, '|]' , process*
 | *process, '[' , chanset expression, '| |' , chanset expression, ']' , process*
 | *process, '| | |' , process*
 | *process, '/_\' , process*
 | *process, '/_\' , expression, '_\' , process*
 | *process, '[_>' , process*
 | *process, '[_\' , expression, '_>' , process*
 | *process, '\\\' , chanset expression*
 | *process, 'startsby' , expression*
 | *process, 'endsby' , expression*
 | *'(' , parametrisation, { ',' , parametrisation } , '@' , process, ')'* , *'(' , expression, { ',' , expression } , ')'*
 | *identifier, ['(' , [expression, { ',' , expression }], ')'*]
 | *process, renaming expression*
 | *replicated process*
 | *'(' , process, ')'*
 ;

action process →
'begin' , { *action paragraph* } , *'@'* , *action* , *'end'*
 ;

replicated process →
';' , *replication declarations* , *'@'* , *process*
 | *'[]'* , *replication declarations* , *'@'* , *process*

| ‘|~|’, *replication declarations*, ‘@’, *process*
 | ‘|||’, *replication declarations*, ‘@’, *process*
 | ‘[]’, *chanset expression*, ‘|’, *replication declarations*, ‘@’, *process*
 | ‘| |’, *replication declarations*, ‘@’, ‘[’, [*chanset expression*], ‘]’, *process*
 ;

action paragraph →
type declarations
 | *value declarations*
 | *function declarations*
 | *operation declarations*
 | *action declarations*
 | *nameset declarations*
 | *state declarations*
 ;

renaming expression →
 ‘[[’, *renaming pair*, { ‘,’, *renaming pair* }, ‘]]’
 | ‘[[’, *renaming pair*, ‘|’ *bind list*, [‘@’, *expression*], ‘]]’
 ;

Note that the current parser only supports a single expression after an identifier in a *renaming pair*; this will be corrected in a future release.

renaming pair →
identifier, { ‘.’, *expression* }, ‘<-’, *identifier*, { ‘.’, *expression* }
 ;

replication declarations →
replication declaration, { ‘,’, *replication declaration* }
 ;

replication declaration →
identifier, { ‘,’, *identifier* }, ‘:’, *type*
 | *identifier*, { ‘,’, *identifier* }, ‘in’ ‘set’, *expression*
 ;

6 Actions

action →

identifier
 | 'Skip'
 | 'Stop'
 | 'Diverge'
 | 'Wait' *expression*
 | *communication*, '->', *action*
 | '[', *expression*, ']', '&', *action*
 | *action*, ';', *action*
 | *action*, '[]', *action*
 | *action*, '|~|', *action*
 | *action*, '/_\'', *action*
 | *action*, '/_', *expression*, '_\'', *action*
 | *action*, '[_>', *action*
 | *action*, '[_', *expression*, '_>', *action*
 | *action*, '\\', *chanset expression*
 | *action*, 'startsby', *expression*
 | *action*, 'endsby', *expression*
 | *action*, *renaming expression*
 | 'mu', *identifier*, { ',', *identifier* }, '@', '(', *action*, { ',', *action* }, ')'
 | *parallel action*
 | *parametrised action*
 | '(', *action*, ')'
 | *instantiated action*
 | *replicated action*
 | *statement*
 ;

communication →

identifier, { *communication parameter* }
 ;

communication parameter →

'?', *bindable pattern*, [':', '(', *expression*, ')']
 | '!', *parameter*
 | '.', *parameter*
 ;

parameter →

identifier

| ‘ (’ *expression* ‘) ’
 | *symbolic literal*
 | *tuple expression*
 | *record expression*
 ;

parallel action →

action, ‘ | | | ’, *action*
 | *action*, ‘ [| |] ’, *nameset expression*, ‘ | ’, *nameset expression*, ‘ | | | ’, *action*
 | *action*, ‘ [’, *chanset expression*, ‘ | | | ’, *chanset expression*, ‘] ’, *action*
 | *action*, ‘ [’, *nameset expression*, ‘ | ’, *chanset expression*, ‘ | | | ’, *chanset expression*,
 ‘ | ’, *nameset expression*, ‘] ’, *action*
 | *action*, ‘ [|] ’, *chanset expression*, ‘ | |] ’, *action*
 | *action*, ‘ [|] ’, *nameset expression*, ‘ | ’, *chanset expression*, ‘ | ’, *nameset*
expression, ‘ | |] ’, *action*
 ;

parametrised action →

‘ (’ *parametrisation*, { ‘ , ’, *parametrisation* }, ‘ @ ’, *action*, ‘) ’
 ;

instantiated action →

parametrised action, ‘ (’, *expression*, { ‘ , ’, *expression* }, ‘) ’
 ;

replicated action →

‘ ; ’, *replication declarations*, ‘ @ ’, *action*
 | ‘ [] ’, *replication declarations*, ‘ @ ’, *action*
 | ‘ | ~ | ’, *replication declarations*, ‘ @ ’, *action*
 | ‘ | | | ’, *replication declarations*, ‘ @ ’, ‘ [’, [*nameset expression*], ‘] ’, *action*
 | ‘ [|] ’, *chanset expression* ‘ | |] ’, *replication declarations*, ‘ @ ’, ‘ [’, [*nameset*
expression], ‘] ’, *action*
 | ‘ | |] ’, *replication declarations*, ‘ @ ’, ‘ [’, [*nameset expression*], ‘ | ’, [*chanset*
expression], ‘] ’, *action*
 ;

7 Statements

statement →

‘ let ’, *local definition*, { ‘ , ’, *local definition* }, ‘ in ’, *action*

| ‘(’, [‘*dcl*’, *assignment definition*, { ‘,’, *assignment definition* }, ‘@’], *action*,
 ‘)’
 | *cases statement*
 | *if statement*
 | ‘*if*’ *non-deterministic alt*, { ‘|’, *non-deterministic alt* }, ‘*end*’
 | ‘*do*’ *non-deterministic alt*, { ‘|’, *non-deterministic alt* }, ‘*end*’
 | ‘*while*’, *expression*, ‘*do*’, *action*
 | ‘*for*’, *bindable pattern*, [‘:’, *type*] ‘*in*’, *expression*, ‘*do*’, *action*
 | ‘*for*’, ‘*all*’, *bindable pattern*, ‘*in set*’, *expression*, ‘*do*’, *action*
 | ‘*for*’, *identifier*, ‘=’, *expression*, ‘*to*’, *expression*, [‘*by*’, *expression*], ‘*do*’,
action
 | [‘[’, [*frame*], [‘*pre*’, *expression*], ‘*post*’, *expression*, ‘]’
 | ‘*return*’, [*expression*]
 | *assign statement*
 | *multiple assign statement*
 | *call statement*
 | *new statement*
 ;

local definition →
value definition
 | *function definition*
 ;

non-deterministic alt →
expression, ‘->’, *action*
 ;

if statement →
 ‘*if*’, *expression*, ‘*then*’, *action*, { *elseif statement* }, [‘*else*’, *action*]
 ;

elseif statement →
 ‘*elseif*’, *expression*, ‘*then*’, *action*
 ;

cases statement →
 ‘*cases*’, *expression*, ‘:’, *cases statement alt*, { ‘,’, *cases statement alt* }, [‘,’,
others statement], ‘*end*’
 ;

cases statement alt →

pattern list, ‘->’, *action*
;

others statement →

‘others’, ‘->’, *action*
;

assign statement →

assignable expression, ‘:=’, *expression*
;

multiple assign statement →

‘atomic’, ‘(’, *assign statement*, ‘;’, *assign statement*, { ‘;’, *assign statement* },
‘)’
;

call statement →

name, ‘(’, [*expression*, { ‘,’, *expression* }], ‘)’
| *assignable expression*, ‘:=’, *name*, ‘(’, [*expression*, { ‘,’, *expression* }], ‘)’
;

new statement →

assignable expression, ‘:=’, ‘new’, *name*, ‘(’, [*expression*, { ‘,’, *expression* }],
‘)’
;

8 Types

type declarations →

‘types’, [*type definition*, { ‘;’, *type definition* }]
;

type definition →

[*qualifier*], *identifier*, ‘=’, *type*, [*type invariant*]
| [*qualifier*], *identifier*, ‘::’, { *field* }, [*type invariant*]]
;

type →

‘ (, *type* , ’
 | *basic type*
 | *quote literal*
 | ‘compose’, *identifier*, ‘of’, { *field* }, ‘end’
 | *type*, ‘|’, *type*, { ‘|’, *type* }
 | *type*, ‘*’, *type*, { ‘*’, *type* }
 | ‘[’, *type*, ‘]’
 | ‘set’ ‘of’, *type*
 | ‘seq’ ‘of’, *type*
 | ‘seq1’ ‘of’, *type*
 | ‘map’, *type*, ‘to’, *type*
 | ‘inmap’, *type*, ‘to’, *type*
 | *function type*
 | *name*
 ;

basic type →

‘bool’ | ‘nat’ | ‘nat1’ | ‘int’ | ‘rat’ | ‘real’ | ‘char’ | ‘token’
 ;

field →

type
 | *identifier*, ‘:’, *type*
 | *identifier*, ‘:-’, *type*
 ;

function type →

discretionary type, ‘+>’, *type*
 | *discretionary type*, ‘->’, *type*
 ;

discretionary type →

type | ‘ () ’
 ;

type invariant →

‘inv’, *pattern*, ‘==’, *expression*
 ;

9 Operations

Operations do not include reactive constructs; while the parser will accept any action in an operation body, the typechecker will only allow statements, the ‘;’ sequential composition operator, and the constant action ‘Skip’. In essence, operation bodies in CML allow only what is allowed in VDM operation bodies.

operation declarations →

```
‘operations’, { operation definition }
;
```

operation definition →

```
explicit operation definition
| implicit operation definition
;
```

explicit operation definition →

```
[ qualifier ], identifier, ‘:’, operation type, identifier, parameters, ‘==’, operation body, [ ‘pre’, expression ], [ ‘post’, expression ]
;
```

operation type →

```
discretionary type, ‘==>’, discretionary type
;
```

operation body →

```
action
| ‘is subclass responsibility’
| ‘is not yet specified’
;
```

implicit operation definition →

```
[ qualifier ], identifier, parameter types, [ identifier type pair list ], [ frame ], [ ‘pre’, expression ], [ ‘post’, expression ]
;
```

frame →

```
‘frame’, var information, { var information }
;
```

var information →

```
'rd', name, { ',', name }, [ ':', type ]
| 'wr', name, { ',', name }, [ ':', type ]
;
```

10 Functions

function declarations →

```
'functions', { function definition }
;
```

function definition →

```
explicit function definition
| implicit function definition
;
```

explicit function definition →

```
[ qualifier ], identifier, ':', function type, identifier, parameters list, '==', function
body, [ 'pre', expression ], [ 'post', expression ], [ 'measure', name ]
;
```

parameters list →

```
parameters, { parameters }
;
```

parameters →

```
(', [ pattern list ], ' )
;
```

implicit function definition →

```
[ qualifier ], identifier, parameter types, identifier type pair list, [ 'pre', expression
], 'post', expression
;
```

parameter types →

```
(', [ pattern list, ':', type, { ',', pattern list, ':', type } ], ' )
;
```

identifier type pair list →
identifier, ':', *type*, { ',', *identifier*, ':', *type* }
 ;

function body →
expression
 | 'is not yet specified'
 | 'is subclass responsibility'
 ;

11 Expressions

expression →
 'self'
 | *name*
 | *old name*
 | *symbolic literal*
 | '(', *expression*, ')'
 | *unary operator*, *expression*
 | *expression*, *binary operator*, *expression*
 | 'let', *local definition*, { ',', *local definition* }, 'in', *expression*
 | 'forall', *bind list*, '@', *expression*
 | 'exists', *bind list*, '@', *expression*
 | 'exists1', *bind*, '@', *expression*
 | 'iota', *bind*, '@', *expression*
 | 'lambda', *type bind list*, '@', *expression*
 | 'is_', '(', *expression*, ',', *type*, ')'
 | 'is_', *basic type*, '(', *expression*, ')'
 | 'is_', *name*, '(', *expression*, ')'
 | 'pre_', '(', *expression*, { ',', *expression* }, ')'
 | 'isofclass', '(', *name*, *expression*, ')'
 | *tuple expression*
 | *record expression*
 | *set expression*
 | *sequence expression*
 | *subsequence*
 | *map expression*
 | *if expression*
 | *cases expression*
 | *apply*
 | *field select*
 | *tuple select*

;

name →*identifier*, [*'.'*, *identifier*]

;

old name →*identifier*, *'~'*

;

unary operator →*'+* | *'-* | *'abs'* | *'floor'* | *'not'* | *'card'* | *'power'* | *'dunion'* | *'dinter'* |
'hd' | *'tl'* | *'len'* | *'elems'* | *'inds'* | *'reverse'* | *'conc'* | *'dom'* | *'rng'* |
'merge' | *'inverse'*

;

binary operator →*'+'* | *'-'* | *'*'* | *'/'* | *'div'* | *'rem'* | *'mod'* | *'<'* | *'<='* | *'>'* | *'>='* | *'='* | *'<>'* | *'or'* |
'and' | *'=>'* | *'<=>'* | *'in'* | *'set'* | *'not'* | *'in'* | *'set'* | *'subset'* | *'psubset'* |
'union' | *'\'* | *'inter'* | *'^'* | *'++'* | *'munion'* | *'<:'* | *'<-:'* | *'>:'* | *'>-:'* |
'comp' | *'**'*

;

tuple expression →*'mk_'*, *'('*, *expression*, *'.'*, *expression*, { *'.'*, *expression* }, *'('*)

;

record expression →*'mk_'*, *'token'*, *'('*, *expression*, *'('*)
| *'mk_'*, *name*, *'('*, [*expression*, { *'.'*, *expression* }], *'('*)

;

set expression →*'{'*, [*expression*, { *'.'*, *expression* }], *'{'*)
| *'{'*, *expression*, *'|'*, *bind list*, [*'@'*, *expression*], *'{'*)
| *'{'*, *expression*, *'.'*, *'...'*, *'.'*, *expression*, *'{'*)

;

sequence expression →

‘[’, [*expression*, { ‘,’, *expression* }], ‘]’
 | ‘[’, *expression*, ‘|’, *set bind*, [‘@’, *expression*], ‘]’
 ;

subsequence →
expression, ‘(’, *expression*, ‘,’, ‘...’, ‘,’, *expression*, ‘)’
 ;

map expression →
 ‘{’, ‘|->’, ‘}’
 | ‘{’, *maplet*, { ‘,’, *maplet* }, ‘}’
 | ‘{’, *maplet*, ‘|’, *bind list*, [‘@’, *expression*], ‘}’
 ;

maplet →
expression, ‘|->’, *expression*
 ;

apply →
expression, ‘(’, [*expression*, { ‘,’, *expression* }], ‘)’
 ;

field select →
expression, ‘.’, *identifier*
 ;

tuple select →
expression, ‘.#’, *numeral*
 ;

if expression →
 ‘if’, *expression*, ‘then’, *expression*, { *elseif expression* }, ‘else’, *expression*
 ;

elseif expression →
 ‘elseif’, *expression*, ‘then’, *expression*
 ;

cases expression →

'cases', expression, ':', cases expression alternatives, [',', 'others' '->' expression], 'end'
;

cases expression alternatives →

pattern list, '->', expression, { ',', pattern list, '->', expression }
;

assignable expression →

'self' { selector }
| identifier { selector }
;

selector →

(', [expression, { ',', expression }], ')
| (', expression, '...', expression, '')
| '#', numeral
| '.', identifier
;

12 Patterns

pattern →

bindable pattern
| match value
;

bindable pattern →

'_'
| identifier
| 'mk_', ('', pattern, ',', pattern list, '')
| 'mk_', name, ('', [pattern list], '')
;

match value →

('', expression, '')
| symbolic literal
;

pattern list →

pattern, { ‘,’ , *pattern* }
;

bind →

set bind
| *type bind*
;

set bind →

pattern, ‘in’ ‘set’, *expression*
;

type bind →

pattern, ‘:’, *type*
;

bind list →

multiple bind, { ‘,’ , *multiple bind* }
;

multiple bind →

pattern list, ‘in’ ‘set’, *expression*
| *pattern list*, ‘:’, *type*
;

type bind list →

type bind, { ‘,’ , *type bind* }
;

13 Lexical Specification

[*Please note: the parser’s implementation of this is still incomplete. For now it’s probably best to stick within the ASCII character set.*]

Unlike the rest of this specification, the rules in this section are sensitive to whitespace; as such, whitespace may not implicitly separate any pair of components in a rule here.

Note that the unicode character categories can be found online at <http://www.fileformat.info/info/unicode/category/index.htm>. The present release of the tool only supports characters below U+0100; support for characters outside of the extended ASCII subset of unicode is planned for a future release.

initial letter → if ‘codepoint < U+0100’ then Any character in categories *Ll*, *Lm*, *Lo*, *Lt*, *Lu*, or the character ‘U+0024’ (‘\\$’) else Any character, excluding categories *Cc*, *Zl*, *Zp*, *Zs*, *Cs*, *Cn*, *Nd*, *Pc*. ;

following letter → if ‘codepoint < U+0100’ then Any character in categories *Ll*, *Lm*, *Lo*, *Lt*, *Lu*, *Nd*, or the characters ‘U+0024’ (‘\\$’), ‘U+0027’ (‘’), and ‘U+005F’ (‘_’) else Any character, excluding categories *Cc*, *Zl*, *Zp*, *Zs*, *Cs*, *Cn*. ;

ascii letter → Any character in the ranges [‘U+0041’,‘U+005A’] and [‘U+0061’,‘U+007A’] --- A-Z and a-z, respectively. ;

character → Is left underdefined, except to note that it may be any unicode character except those that conflict with the lexical rule that uses the character class. For example, character does not include ‘\’ in the *character literal* rule. ;

identifier →
initial letter, { *following letter* }
 ;

digit →
 ‘0’ | ‘1’ | ‘2’ | ‘3’ | ‘4’ | ‘5’ | ‘6’ | ‘7’ | ‘8’ | ‘9’
 ;

hex digit →
digit | ‘a’ | ‘b’ | ‘c’ | ‘d’ | ‘e’ | ‘f’ | ‘A’ | ‘B’ | ‘C’ | ‘D’ | ‘E’ | ‘F’
 ;

numeral →
digit, { *digit* }
 ;

symbolic literal →
numeric literal
 | *boolean literal*
 | *nil literal*
 | *character literal*
 | *text literal*
 | *quote literal*

;

numeric literal →*decimal literal*| *hex literal*

;

exponent →('E' | 'e'), ['+' | '-'], *numeral*

;

decimal literal →*numeral*, ['.' , *digit*, { *digit* }], [*exponent*]

;

hex literal →('0x' | '0X'), *hex digit*, { *hex digit* }

;

boolean literal →

'true' | 'false'

;

nil literal →

'nil'

;

character literal →'r', *character*, 'r'| 'r', *escape sequence*, 'r'

;

escape sequence →'\\' | '\r' | '\n' | '\t' | '\f' | '\e' | '\a' | '\"' | '\r' | '\x', *hex digit*, *hex digit*| '\u', *hex digit*, *hex digit*, *hex digit*, *hex digit*| '\c', *ascii letter*

;

text literal →

‘”’, { *character* | *escape sequence* }, ‘”’
;

quote literal →

‘<’, *identifier*, ‘>’
;

References

- [BCW14] Jeremy Bryans, Samuel Canham, and Jim Woodcock. CML definition 4. Technical report, COMPASS Deliverable, D23.5, March 2014. Available at <http://www.compass-research.eu/>.
- [Col13] Joey W. Coleman. Third release of the COMPASS tool — CML grammar reference. Technical report, COMPASS Deliverable, D31.3c, November 2013.

Index of Rule Definitions

- action, 9, 10, 12–15, 17
 - definition*, 12
- action declarations, 11
 - definition*, 9
- action definition, 9
 - definition*, 9
- action paragraph, 10
 - definition*, 11
- action process, 10
 - definition*, 10
- apply, 19
 - definition*, 21
- ascii letter, 25
- assign statement, 14, 15
 - definition*, 15
- assignable expression, 15
 - definition*, 22
- assignment definition, 8, 14
 - definition*, 8
- basic type, 16, 19
 - definition*, 16
- binary operator, 19
 - definition*, 20
- bind, 19
 - definition*, 23
- bind list, 9, 11, 19–21
 - definition*, 23
- bindable pattern, 7, 12, 14, 22
 - definition*, 22
- boolean literal, 24
 - definition*, 25
- call statement, 14
 - definition*, 15
- cases expression, 19
 - definition*, 22
- cases expression alternatives, 22
 - definition*, 22
- cases statement, 14
 - definition*, 14
- cases statement alt, 14
 - definition*, 15
- channel declarations, 7
 - definition*, 7
- channel name declarations, 7
 - definition*, 7
- chanset declarations, 7
 - definition*, 7
- chanset definition, 8
 - definition*, 8
- chanset expression, 8–13
 - definition*, 9
- character, 25, 26
- character literal, 24
 - definition*, 25
- class declaration, 7
 - definition*, 9
- class paragraph, 9
 - definition*, 10
- communication, 12
 - definition*, 12
- communication parameter, 12
 - definition*, 12
- decimal literal, 25
 - definition*, 25
- digit, 24, 25
 - definition*, 24
- discretionary type, 16, 17
 - definition*, 16
- elseif expression, 21
 - definition*, 21
- elseif statement, 14
 - definition*, 14
- escape sequence, 25, 26
 - definition*, 25
- explicit function definition, 18
 - definition*, 18
- explicit operation definition, 17
 - definition*, 17
- exponent, 25
 - definition*, 25
- expression, 7–23
 - definition*, 19
- field, 15, 16
 - definition*, 16
- field select, 19
 - definition*, 21
- following letter, 24
- frame, 14, 17
 - definition*, 17

- function body, 18
 - definition*, 19
- function declarations, 7, 10, 11
 - definition*, 18
- function definition, 14, 18
 - definition*, 18
- function type, 16, 18
 - definition*, 16
- hex digit, 25
 - definition*, 24
- hex literal, 25
 - definition*, 25
- identifier, 7–12, 14–22, 26
 - definition*, 24
- identifier type pair list, 17, 18
 - definition*, 18
- if expression, 19
 - definition*, 21
- if statement, 14
 - definition*, 14
- implicit function definition, 18
 - definition*, 18
- implicit operation definition, 17
 - definition*, 17
- initial letter, 24
- instance variable definition, 8
 - definition*, 8
- instantiated action, 12
 - definition*, 13
- invariant definition, 8
 - definition*, 8
- local definition, 13, 19
 - definition*, 14
- map expression, 19
 - definition*, 21
- maplet, 21
 - definition*, 21
- match value, 22
 - definition*, 22
- model
 - definition*, 7
- model paragraph, 7
 - definition*, 7
- multiple assign statement, 14
 - definition*, 15
- multiple bind, 23
 - definition*, 23
- name, 15, 16, 18–20, 22
 - definition*, 20
- nameset declarations, 11
 - definition*, 8
- nameset definition, 8
 - definition*, 8
- nameset expression, 8, 13
 - definition*, 9
- new statement, 14
 - definition*, 15
- nil literal, 24
 - definition*, 25
- non-deterministic alt, 14
 - definition*, 14
- numeral, 21, 22, 25
 - definition*, 24
- numeric literal, 24
 - definition*, 25
- old name, 19
 - definition*, 20
- operation body, 17
 - definition*, 17
- operation declarations, 10, 11
 - definition*, 17
- operation definition, 10, 17
 - definition*, 17
- operation type, 17
 - definition*, 17
- others statement, 14
 - definition*, 15
- parallel action, 12
 - definition*, 13
- parameter, 12
 - definition*, 12
- parameter types, 17, 18
 - definition*, 18
- parameters, 17, 18
 - definition*, 18
- parameters list, 18
 - definition*, 18
- parametrisation, 8–10, 13
 - definition*, 9
- parametrisation qualifier, 9
 - definition*, 9
- parametrised action, 12, 13
 - definition*, 13

- pattern, 16, 22, 23
 - definition*, 22
- pattern list, 15, 18, 22, 23
 - definition*, 23
- process, 8, 10, 11
 - definition*, 10
- process declaration, 7
 - definition*, 8
- qualifier, 7, 8, 15, 17, 18
 - definition*, 7
- quote literal, 16, 24
 - definition*, 26
- record expression, 13, 19
 - definition*, 20
- renaming expression, 10, 12
 - definition*, 11
- renaming pair, 11
 - definition*, 11
- replicated action, 12
 - definition*, 13
- replicated process, 10
 - definition*, 10
- replication declaration, 11
 - definition*, 11
- replication declarations, 10, 11, 13
 - definition*, 11
- selector, 22
 - definition*, 22
- sequence expression, 19
 - definition*, 20
- set bind, 21, 23
 - definition*, 23
- set expression, 19
 - definition*, 20
- state declarations, 10, 11
 - definition*, 8
- statement, 12
 - definition*, 13
- subsequence, 19
 - definition*, 21
- symbolic literal, 13, 19, 22
 - definition*, 24
- text literal, 24
 - definition*, 26
- tuple expression, 13, 19
 - definition*, 20
- tuple select, 19
 - definition*, 21
- type, 7–9, 11, 14–16, 18, 19, 23
 - definition*, 15
- type bind, 23
 - definition*, 23
- type bind list, 19
 - definition*, 23
- type declarations, 7, 10, 11
 - definition*, 15
- type definition, 15
 - definition*, 15
- type invariant, 15
 - definition*, 16
- unary operator, 19
 - definition*, 20
- value declarations, 7, 10, 11
 - definition*, 7
- value definition, 7, 14
 - definition*, 7
- var information, 17
 - definition*, 18